INSTANT REPLAY 3

A World Standard for audio clip playout, with a host of new features.

- Larger RGB backlit buttons.
- Playout of wav and mp3 files.
- Intuitive navigation of file system and operations.
- Full color touchscreen provides detailed information on content.

INSTANT REPLAY

в

27

25 26

16

34

29

35 36 31 38 39

AG

28

6

24

- 58 GB of internal solid state memory.
- Ethernet network file sharing and FTP.

- Optional Dante® audio over IP.
- Play directly from externally attached
- USB drives or copy to internal memory.
- Built in editor allows setting of head and tail points + fade-in / fade-out. - Silent operation.
- Backup and restore system settings and content to USB drive.

INSTANT REPLAY 3 Front Panel



- 1.50 Hot Keys with 50 banks for immediate playout of audio clips
- 2. Full color touch screen with rear access USB port*
- 3. Soft keys for keyboard access to menu items
- 4. Power On/Off button
- 5. Direct access keys enable quick access to common functions
- 6. Navigation keys for movement within the screen
- 7. Simple standard transport controls

Audio Performance

Audio Format	16 or 24 bit stereo, 44.1, 48, 88.2 or 96k
	sample rate. Automatic output sample
	rate conversion.
Analog Inputs	Balanced XLR or Unbalanced RCA
Analog Outputs	Balanced XLR or Unbalanced RCA
Digital I/O	AES/EBU XLR. IEC958 Type II or AES-3id RCA
Ethernet audio I/O	Optional Dante [®] interface


General Specifications

Total Storage Time	Approx. 85hrs for wav, 1000hrs+ for mp3**
Internal Storage	58GB, solid state
File Type Support	Recording - wav, Playout - wav or mp3
Display	5″ color touchscreen
Keyboard	Virtually silent, soft touch, RGB backlit

* USB ports are for use with memory keys, standard keyboard and mouse only.

**Storage time based on 48Khz, 16bit wav and 128bit mp3. Actual storage time will vary.

Specifications Rear Panel I/O



- 1. USB ports for keyboard, mouse or external memory devices*
- 2. Ethernet network port for FTP and file share network access
- 3. 26 pin GPIO port for clip triggering and signaling
- 4. IEC-958 II or AES-75 ohm digital input / output on RCA jacks
- 5. AES/EBU Digital input / output on XLR connectors
- 6. Optional Dante[®] Ethernet for IP based audio input and output
- 7. Balanced analog output on XLR connectors
- 8. Balanced analog input on XLR connectors
- 9. Unbalanced analog input / output on RCA jacks
- 10. Power connection
- 11. 1/4" headphone jack with Preview function to silence main outputs.

Mechanical & Misc

Dimensions	1
	(2
Weight	5.
Country of Origin	U

1.56″D x 17.32″W x 1.75″H 294mm x 440mm x 44.5mm) 5.76Lbs (2.62Kg) (Unit only) JSA

www.360systems.com

For support contact 818-991-0360 or info@360systems.com

©2021, 360 Systems, Specifications subject to change without notice. Instant Replay and 360 Systems are trademarks of 360 Systems. Other names and logos are used for reference only and are the property of their respective owners. Dante® is a trademark of Audinate Pty Ltd.