

SPECIFICATIONS

SOURCE

400W LED Engine
Color Temperature: 6900k (+/-350k)
20,000 Hour Average LED Life*

*May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

PHOTOMETRIC DATA

14,500 Total Lumens
CRI: 64 (80 or 90 with HCRI Filter)

EFFECTS

4-Facet Circular & 6-Facet Linear Rotating Prisms
2x Frost Filters (Light and Heavy)
Motorized Zoom: 3°~52°
Motorized Focus
Electronic Dimming & Strobe: 1-20Hz

COLOR

Full CMY color mixing
Variable CTO (3200K to 8500K)
Colors Wheel with 7 dichroic colors (Includes High CRI Filter in slot 7)

GOBOS

(2) Gobo Wheels
#1 - (8) Rotating Glass Gobos (Interchangeable and Indexable)
#2 - (10) Static Glass Gobos

CONTROL / CONNECTIONS

(3) DMX Channel Modes - Basic (26ch) / Standard (31ch) / Extended (40ch)
DMX, RDM, sACN and ArtNet
Aria X2 Wireless Management System
NFC System
6 Button Touch Control Panel
Full Color 180° Reversible LCD Menu Display
8 / 16 Bit Resolution Adjustable Movement
RJ45 In/Thru Network Ports
5 pin XLR DMX In/Out
IP65 Locking Power In/Out
With Wired Digital Communication Network

PAN / TILT

Pan: 540/630-degrees
Tilt: 270-degrees
Pan & Tilt Locks

SIZE / WEIGHT

Length: 14.2" (360mm)
Width: 9.3" (234mm)
Vertical Height: 23.5" (597mm)
Weight: 44.5 lbs. (20.2kg)

ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz
Max Power Consumption: 450W @ 220V.
Max ambient temperature: -13°F to 113°F (-25°C to 45°C)
Max housing temperature: TBD

TECHNICAL DATA

DB Rating @ 3ft.: ?dB
BTU: 0.43
BTU/H: 1,534.50

APPROVALS / RATINGS

CE, FCC, cETLus (Control # 4010765), IP20



INCLUDED ACCESSORIES

(1) Power cable
(2) Omega bracket