

SPECIFICATIONS

Source:

- 19 x 60-Watt RGBL LEDs (50,000 hr.)
- CRI: 84.2
- TM30 Rf: 84.7
- TM30 Rg: 99.8
- Color Temperature: 2700K ~ 10,000K
- 54,400 lux / 4.3° beam @ 16' (5m)
- 2,090 lux / 28.3° beam @ 16' (5m)
- Lumens: 17,000 (Zoomed Out, Full On)

Features:

- Moving Light Pixel Wash
- Individual Pixel Control
- Built-In Pixel Effect Programs
- Aria X2 Wireless Management System
- Electronic Strobe / Dimmer
- Pan/Tilt: 540/630 x 243
- Motorized Zoom
- Beam Angle: 5° ~ 38°
- Field Angle: 8° ~ 56°
- Color Calibrated Pixels so units match from batch to batch
- Virtual CMY DMX Control Modes
- Virtual Foreground and Background Color Wheel Control
- Selectable LED Refresh Rates (900 Hz~25K Hz)
- Selectable Dim Modes: Standard, Stage, TV, Arch., Theatre, Stage 2 and user settable Dim Speed (0.1S~10S)
- 4 Dim Curves: Square, Linear, Inv. Square and S. Curve
- 0-100% smooth dimming
- Fan Cooled

Colors:

- 19x RGBL LEDs (Red, Green, Blue and Lime)
- Virtual CMY DMX Control Modes
- Virtual Foreground and Background Color Wheel Control
- Built-In Color Macros
- 2,700K ~ 10,000K Linear White Color Temperature Control
- Color Temperature Presets: 2,700, 3,000, 3,200, 4,000, 4,500, 5,000, 5,600, 6,500, 8,000 and 10,000K

Control:

- 6 DMX Modes (22, 31, 40, 104, Standard CMY 31, Extended CMY 34)
- Color LCD display with 6-button function menu
- Control: DMX512, ArtNet, sACN, KlingNet and Aria X2 Wireless Management System
- Built-In Effect Pixel Programs with Speed and Fade Control
- RDM (Remote Device Management) compliant
- With Wired Digital Communication Network

Pan/Tilt:

- Pan: 540/630 degrees
- Tilt: 243 degrees
- 16-Bit Fine Pan & Tilt
- Pan & Tilt Locks

Connections:

- DMX Connections: IP65-rated Locking In/Out XLR Sockets
- IP65-rated Locking In/Out RJ45 Network Sockets
- Power Connections: IP65-rated Locking In/Out Power Sockets

Electrical:

- Multi-voltage operation: 100-240V, 50/60Hz
- Max power consumption: 1400W (11.85Amps) @ 120V. 1350W (6.38Amps) @ 220V.

Dimensions & Weight:

- Dimensions (LxWxH): 12.5"L x 17.04"W x 20.36"H (318x433x517mm)
- Weight: 60.8lbs (27.6kg)

What's Included:

- 180mm Omega Brackets (2x)
- 1x 1.83M, IP65-rated locking power cable
- Safety Cable

Approvals / Rating:

- cETLus (Control # 4010765)
- CE Certified
- FCC
- UKCA
- IP65



IP65