

Lace-up Hoisting Grip for 1-1/4 in coaxial cable and elliptical waveguide 64



Product Classification

| | |
|----------------------|---|
| Product Type | Hoisting grip |
| Ordering Note | CommScope® standard product in the United States and Canada |

General Specifications

| | |
|-------------------------------------|-----------------------|
| Attachment Spacing Intervals | 60.96 m 200 ft |
| Hoisting Grip Type | Lace-up hoisting grip |
| Support Clamp | Not included |
| Tool Type | Hoisting grip |

Dimensions

| | |
|-------------------------------|-----------------|
| Grip Length, minimum | 635 mm 25 in |
| Leader Length, minimum | 203.2 mm 8 in |
| Nominal Size | 1-1/4 in |

Electrical Specifications

| | |
|---------------------------|--------|
| Return Loss Effect | 0.1 dB |
| DTF Effect | 0.1 dB |

Material Specifications

| | |
|----------------------|-----------------|
| Material Type | Stainless steel |
|----------------------|-----------------|

Mechanical Specifications

| | |
|---------------------------|---------------------|
| Pull Load Capacity | 408.233 kg 900 lb |
|---------------------------|---------------------|

Packaging and Weights

29961

| | |
|---------------------------|--------------------|
| Height, packed | 55.88 mm 2.2 in |
| Width, packed | 236.22 mm 9.3 in |
| Length, packed | 236.22 mm 9.3 in |
| Packaging quantity | 1 |
| Weight, gross | 0.38 kg 0.838 lb |

Regulatory Compliance/Certifications

Agency

ISO 9001:2015

REACH-SVHC

ROHS



Classification

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

Compliant