

Lace-up Hoisting Grip for 1/2 in coaxial cable and elliptical waveguide 180 and 220



## Product Classification

<b>Product Type</b>	Hoisting grip
<b>Ordering Note</b>	CommScope® standard product in the United States and Canada

## General Specifications

<b>Attachment Spacing Intervals</b>	60.96 m   200 ft
<b>Hoisting Grip Type</b>	Lace-up hoisting grip
<b>Support Clamp</b>	Not included
<b>Tool Type</b>	Hoisting grip

## Dimensions

<b>Grip Length, minimum</b>	254 mm   10 in
<b>Leader Length, minimum</b>	177.8 mm   7 in
<b>Nominal Size</b>	1/2 in

## Electrical Specifications

<b>Return Loss Effect</b>	0.1 dB
<b>DTF Effect</b>	0.1 dB

## Material Specifications

<b>Material Type</b>	Stainless steel
----------------------	-----------------

## Mechanical Specifications

<b>Pull Load Capacity</b>	226.796 kg   500 lb
---------------------------	---------------------

## Packaging and Weights

# 43094

---

<b>Height, packed</b>	43.18 mm   1.7 in
<b>Width, packed</b>	187.96 mm   7.4 in
<b>Length, packed</b>	246.38 mm   9.7 in
<b>Packaging quantity</b>	1
<b>Weight, gross</b>	0.2 kg   0.441 lb

## Regulatory Compliance/Certifications

### Agency

CHINA-ROHS

ISO 9001:2015

REACH-SVHC

ROHS

### Classification

Below maximum concentration value

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on [www.commscope.com/ProductCompliance](http://www.commscope.com/ProductCompliance)

Compliant

