


# 43211A



Butterfly Hanger for 1/2 in or 3/8 in coaxial cable and elliptical waveguide 180, 220, and 240

## Product Classification

Product Type	Hanger kit
Ordering Note	CommScope® standard product in Mexico, Central America, and South America   CommScope® standard product in the United States and Canada

## General Specifications

Cables per Hanger	1
Color	Silver
Hanger Type	Standard butterfly hanger
Mounting	3/8 in (M10) drilled cable ladder

## Dimensions

Height	31.75 mm   1.25 in
Width	38.1 mm   1.5 in
Length	40.64 mm   1.6 in
Compatible Diameter, maximum	16.256 mm   0.64 in
Compatible Diameter, minimum	10.414 mm   0.41 in
Nominal Size	1/2 in

## Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

## Material Specifications

Material Type	Stainless steel
---------------	-----------------

# 43211A

## Mechanical Specifications

**Vibration Survival** =4 hours at resonant frequency

## Environmental Specifications

**Operating Temperature** -40 °C to +85 °C (-40 °F to +185 °F)

**Corrosion Resistance, minimum with no degradation** =500 hours in salt spray chamber

**Environmental Strength Capability** Double cable weight

## Packaging and Weights

**Height, packed** 14.8 cm | 5.827 in

**Width, packed** 10.6 cm | 4.173 in

**Length, packed** 9 cm | 3.543 in

**Packaging quantity** 10

**Weight, gross** 0.34 kg | 0.75 lb

## Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

