



## SnapStak® Hanger for 1-1/4 in coaxial cable

### Product Classification

<b>Product Type</b>	Hanger kit
<b>Product Brand</b>	SnapStak®
<b>Ordering Note</b>	CommScope® standard product in Asia Pacific   CommScope® standard product in Mexico, Central America, and South America   CommScope® standard product in the United States and Canada

### General Specifications

<b>Cables per Hanger</b>	1
<b>Color</b>	Silver
<b>Hanger Type</b>	Snap-in hanger
<b>Mounting</b>	3/4 in drilled cable ladder

### Dimensions

<b>Height</b>	40.894 mm   1.61 in
<b>Maximum Stack Height</b>	2
<b>Width</b>	40.132 mm   1.58 in
<b>Length</b>	81.026 mm   3.19 in
<b>Compatible Diameter, maximum</b>	43.18 mm   1.7 in
<b>Compatible Diameter, minimum</b>	37.592 mm   1.48 in
<b>Nominal Size</b>	1-1/4 in

### Electrical Specifications

<b>Return Loss Effect</b>	0.1 dB
<b>DTF Effect</b>	0.1 dB

# SSH-114

---

## Material Specifications

**Material Type** Stainless steel

## Mechanical Specifications

**Vibration Survival** =4 hours at resonant frequency

## Environmental Specifications

**Operating Temperature** -40 °C to +85 °C (-40 °F to +185 °F)

**Corrosion Resistance, minimum with no degradation** =500 hours in salt spray chamber

**Environmental Strength Capability** Double cable weight

## Packaging and Weights

**Height, packed** 22 cm | 8.661 in

**Width, packed** 14.6 cm | 5.748 in

**Length, packed** 14.8 cm | 5.827 in

**Packaging quantity** 10

**Weight, gross** 0.52 kg | 1.146 lb

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant



## \* Footnotes

**Maximum Stack Height** Fiber, Hybrid, Power