

# Product data sheet

Specifications



## APC Smart-UPS, Line Interactive, 750VA, Lithium-ion, Rack/Tower, 2U, 120V, 6x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, Short Depth, AVR, LCD

SMTL750RM2UC

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	600 W
Rated power in VA	750 VA
Plug standard	NEMA 5-15P
Nb of power socket outlets	6 NEMA 5-15R
Number of rack unit	2U
Cable length	8 ft (2.44 m)
Number of cables	1
Battery Type	Li-Ion (Lithium Ion)
Provided equipment	CD with software Documentation CD Installation guide Rack Mounting support rails Smart UPS signalling RS-232 cable USB cable

### Physical

Color	Black
Height	3.39 in (8.6 cm)
Width	17.24 in (43.8 cm)
Depth	12.52 in (31.8 cm)
Net Weight	34.00 lb(US) (15.42 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	1
USB compatible	Yes

## Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Efficiency at full load	75...154 V adjustable 82...144 V

## Output

Max Configurable Power (Watts)	600 W
Harmonic distortion	Less than 5%
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
Topology	Line Interactive
Waveform Type	Sine wave

## Conformance

Product Certifications	NOM
Standards	CSA C22.2 No 107.3 FCC Part 15 class A UL 1778 UL 1973
Equipment protection policy	Lifetime : \$150000

## Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-40...95 °F (-40...35 °C)
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...25000 ft (0.00...7620.00 m)
Acoustic level	41 dBA
Heat dissipation	70 Btu/h

## Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h

## Communications & Management

Free slots	1
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

Surge energy rating	680 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

## Ordering and shipping details

GTIN	731304341994
Package weight(Lbs)	39.00 lb(US) (17.69 kg)

## Packing Units

Package 1 Height	9.02 in (22.9 cm)
Package 1 width	22.99 in (58.4 cm)
Package 1 Length	18.58 in (47.2 cm)
Number of Units in Package 3	16

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------