



**BLS-BV095HD (V-Mount)**  
**BLS-BG095HD (Gold Mount®)**

**Main Features**

- 12 Amp Maximum Sustained Draw
- GRANITE Shock-Proof Construction
- GRANITE Link Wi-fi Connectivity
- IP54 Rating – Rainproof
- Long-lasting 92-Watt Hour Capacity
- Dual D-taps
- D-tap Charging Enabled
- Status given thru 5 LEDs and/or the GRANITE Link App
- Safety Disconnects on Main and D-tap Connectors
- Reusable Contact Safety Cover Provided
- Intelligent Power Mode Management
- Compatible with Most Charger Brands
- Advanced Design for Easier Service
- Carry-on flight approved (see regs.)



**Product Description**

The 095HD batteries have been devised for primarily for cameras with a lower profile that require up to 12A current draws such as RED® DMSC, BMD cameras and such or smaller lights. These batteries are designed to provide a low profile so as not to restrict operation and connections. The highest quality raw materials with innovative design and construction techniques, BLUESHAPE has been able to create these professional batteries that border on the limits of currently available technology.

All GRANITE TWO batteries have an embedded Wi-Fi module that is the core of the GRANITE Link architecture. Data can be transmitted via the free GRANITE Link App, available for Android or iOS. Real-time usage or charging data is available as well as battery health indicators. The battery can also communicate with a PC through our BSMON.

The battery is protected from overdraw though the main contacts without fuses. If the battery output exceeds the limit, it will go cease operating but will again resume operation a few seconds after the overload condition has been removed

The D-tap socket output is regulated at 70W. If overdrawn the power is automatically resumed by removing the overload condition from the D-tap.

**Recommended Accessories**

Product	BG140HD	BV140HD
CHARGER, 4 PLACE		CVS4XL
CHARGER, 2 PLACE	CGTR2P	CVTR2P
CHARGER, 1 PLACE POUCH	CGTR1M-45	CVTR1M-45
CHARGER, D-TAP	CDT-45	CDT-45
PT TO DUAL USB ADAPTER	PT2USB	PT2USB
GRANITE LINK WI-FI ACCESS POINT	GRANITE LINK AP	GRANITE LINK AP

**What's in the Box?**

Picture	Name	Qty
	095HD Battery	1
	Contact Cover	1



**BLS-BV095HD (V-Mount)**  
**BLS-BG095HD (Gold Mount®)**

**Specifications**

Parameter	BG095HD BV095HD
Nominal Voltage	14.4 V
Operating Voltage Range	10.0V - 16.8V
Nominal Capacity	9.9 Ah
Nominal Energy	92-Watt Hour
Max Continuous Discharge	12 A
Max D-tap Combined Output	Shared with total output of battery via terminals
Operating Temperature	-4° ~140°F (-20° ~ +60°C)
IP Rating	IP54
Wi-fi Module	Wi-Fi 2.4 GHz - 802.11 b/g/n
Dimensions	
L x W x H (inches)	4.56 x 3.74 x 2.08
L x W x H (mm)	116 x 95 x 53
Warranty (months)	18; with registration, 24
Weight	1.92 lbs (.87Kg)



BG095HD


BV095HD

**Charging Times in Minutes**

Charging to 90%, to 100% with fan on*		
Product	BG095HD	BV095HD
CDT-45	85, 115	85, 115
CGTR1M-45 CVTR1M-45	85, 115	85, 115
CGTR2P* CVTR2P*	57, 77	57, 77
CVS4XL*	n/a	57, 77
Charging to 90%, to 100% with fan off*		
Product	BG290HD plus	BV290HD plus
CDT-45	83, 113	83, 113
CGTR1M-45 CVTR1M-45	110, 150	110, 150
CGTR2P* CVTR2P*	35, 45	35, 45
CVS4XL*	n/a	70, 100

**Sales & Shipping Information**

Product Name	BG095HD	BV095HD
MFGR #	NCBNEG3P-HDM	NCBNEV3P-HDM
SKU/EAN	8032774981973	8032774981935
MAP	TBD	
Package Size	7.7x 5.5 x 2.7" (19.6x14x6.9cm)	
Net Weight	2.3 lbs	
Gross Weight	2.5 lbs	
Carton Quantity	12	
Carton Dimensions	16x12x10.5" 40x30x26 cm	
Carton Weight	13.2 lbs 4.8Kg	



GRANITE Link App, main two pages

Contact BOLD Distribution, 615.431.2499  
 info@bolddistribution.us 1/1/2022