

BLS-CGTR1M-45 Charger (Gold Mount©) BLS-CVTR1M-45 Charger (V-Mount©)

Main Features

- Cordova-style Pouch
 - Elegant and Functional
 - Easily Transportable
- Fast Charging
 - Up to 4.5 Amp per Channel
- Charge any Brand of Batteries
- Cordova-style Pouch
- Short-circuit and Overload Internal Protection
- Consistent Current and Voltage
- Pre-charge Feature for Battery Protection
- High-quality Plate Adapter Base
- Lightweight and Compact



Product	Use



Product Description

The C_TR1M-45 is designed as a handy, extremely portable to simplify battery charging and ensure quick charger availability whenever and wherever required. It has an elegant appearance the belies its durability and longevity.

This pouch charger has many of the features of a studio charger. A pre-charge function protects heavily discharged cells against high currents until their voltages rise to a safe level. The 4.5A current ensures fast charging of even larger batteries. Short-circuit and protection is also provided. The charger provides a consistent current and voltage during the charging process.

The interface plate is a high quality BLUESHAPE V-mount or 3-stud plate – the same as used on cameras or other devices – attached to a metal plate inserted into a pocket in the pouch to provide a quality interface that lasts for years.

What's in the Box?

Picture	Name	Qnty
	C_TR1M-45 Charger	1
	AC cable	1



BLS-CGTR1M-45 Charger (Gold Mount©) BLS-CVTR1M-45 Charger (V-Mount©)

Specifications



CGTR1M-45



CVTR1M-45

Charging Performance

C_TR1M-45 Charging Performance				
Approximate charging time per channel (minutes)				
		CC		
Battery	Battery	Rate	State of Charge %	
	C		90%	
Model	Capacity	(0.5C)	(min)	100% (min)
B_095HD	95Wh	4.5A	141	192
B_140HD	143Wh	4.5A	192	243
B_90	95Wh	4.5A	141	192
B_100HD+	100Wh	4.5A	141	192
B_150	150Wh	4.5A	192	256
B_190HD+	193Wh	4.5A	269	346
B_290HD+	290Wh	4.5A	397	499

Contact BOLD Distribution, 615.431.2499	
info@bolddistribution.us	1/1/22

NCCVTR1M-45 8032274982130

Parameter	CGTR1M-45 CVTR1M-45
Input Voltage	AC 100-240V 47-63Hz
Output Voltage, Main	DC 16.8V 4.5A max
Output Connector	Battery plate
Operating Temperature	32° ~ 113°F (0° ~ +45°C)
Storage Temperature	-4° ~ 149°F (-20° ~ +65°C)
Indicator	None
Dimensions	
L x W x H (inches)	31.5 x 70.9 x 35.4"
L x W x H (cm)	80 x 180 x 90cm
Warranty	18 Months, 24 w/reg.
Weight	2.2 lbs (1.0Kg)

Sales and Shipping Information

Product Name	CGTR1M-45	CVTR1M-45	
MFGR #	NCCGTR1M-45	NCCVTR1M-45	
SKU/EAN			
MAP	\$305		
Package Size	9.1x7.4x3.0" 23x18.5x7.6cm		
Net Weight	2.4 lbs, 1.1Kg		
Gross Weight	2.6lbs, 1.2Kg		
Carton Quantity	1		
Carton	9.1x7.4x3.0"		
Dimensions	23x18.5x7.6cm		
Carton Weight	2.6lbs, 1.2Kg		