

# Ariane encore | AUDIO LEVELLER



## Double award winning 'Ariane' rules when it comes to transparent RMS levelling.

For most radio engineers, the Ariane needs no introduction. It pre-processes and brings less capable broadcast boxes to life, or it protects an STL - or is a standalone streaming processor.

The transparent sound is well known about, mainly from the sophisticated IDR window gating technology which effectively puts this processor into a state of frozen activity for 90% of operation. It reacts occasionally, quickly and then goes to sleep. Has to be heard to be believed. Hearing is believing.

## Why you'll never regret choosing the Ariane encore.

- **Ariane RMS audio levelling keeps your audio loud**, free from pumping, and with a touch of stereo enhancement if required. This award winning AGC will rock your audio.
- **A unique dynamic release window gating system freezes gain control** for 90% of the time, offering fast responding but impossible to 'hear in operation' audio control.
- **Multi-mode operation provides flexibility**, with the Sum and difference mode offering controllable stereo enhancement, and multi-path reduction for FM radio stations.
- **HTML5, FTP, Telnet, SNMP & RS232 Remote Control**  
Control your processor from anywhere in the world.
- **A flexible and versatile action and alerts system** brings together back panel GPIO at digital and analogue levels of your choosing, integrating it with an easy to set up 'do this when' and 'do this now' set of actions.

### SPECIFICATION

<b>PROCESSING</b>	
AGC	4 band stereo or sum & difference
Protection limiter	Dual band look-ahead
Crossover	4 band adjustable
<b>ANALOG INPUT</b>	
	+4 dBu
Nom. input level	+24 dBu
Max input level	XLR balanced EMI suppressed
Connectors	24 bit
A/D conversion	<0.01%
<b>ANALOG OUTPUT</b>	
Analog output	0-24 dBu adjustable
Connectors	XLR balanced EMI suppressed
D/A conversion	24 bit
<b>DIGITAL INPUT (AES/EBU)</b>	
Sampling rate	32-192 kHz (MPX over AES ready)
Connector	XLR balanced EMI suppressed
Nominal input level	-20 dBfs
<b>DIGITAL OUTPUT (AES/EBU)</b>	
Sampling rate	32-192 kHz (MPX over AES ready)
Connector	XLR balanced EMI suppressed
Level	-32 - 0 dBfs adjustable
<b>Remote Control</b>	
Connectors	Serial, USB A, USB B, RJ45
Protocols	HTTP (browse, mobile, API), SNMP, TELNET, FTP, SMTP, RS232
<b>OTHER</b>	
Power	90 - 260 VAC, 50/60Hz, 25W IEC connector
Environmental	-20°C - 50°C / 0-90% RH, non-condensing
Size (inch)	19" W x 1.73" H x 9.84" D
Size (mm)	44mm x 482mm x 200mm
Weight	1.6 Kg
Warranty	<b>4 year limited warranty</b>

