

8. Specifications

Input	VGA x 1 HDMI x 1 HD/SD-SDI x 1 Analog Audio L/R
Output	SDI x 2 HDMI x 1 SDI Loop thru BNC (front panel)
Micro USB	Firmware upgrade Aspect ratio mode selection
Video Input Format	SDI (YUV) 1080p60/59.94/50, 1080p30/29.97/25/24/23.98 1080psf30/29.97/25/24/23.98 1080i60/59.94/50, 720p60/59.94/50 525i, 625i HDMI (YUV / RGB) 1080p60/59.94/50, 1080p30/29.97/25/24/23.98 1080psf30/29.97/25/24/23.98 1080i60/59.94/50, 720p60/59.94/50 480p, 576p, 480i, 576i 800x600@60Hz, 1024x768@60Hz, 1280x1024@60Hz 1366x768@60Hz, 1400x1050@60Hz, 1600x1200@60Hz VGA (RGB) 800x600@60Hz, 1024x768@60Hz, 1280x1024@60Hz 1366x768@60Hz, 1400x1050@60Hz, 1600x1200@60Hz 1280x720@60Hz, 1920x1080@60Hz
Video Output Format	SDI / HDMI 1080p60/59.94/50, 1080p30/29.97/25/24/23.98 1080i60/59.94/50, 720p60/59.94/50 525i, 625i

Audio Format	Input Analog Audio L/R : stereo audio SDI / HDMI embedded audio up to 8CH, 48KHz, PCM audio HDMI embedded audio up to 8CH, 44.1/48/96KHz, PCM audio Output SDI embedded audio up to 8CH, 48KHz, PCM audio HDMI embedded audio up to 8CH, 48KHz, PCM audio
Operating Temperature	0~40°C [32~104°F]
Storage Temperature	-10~ +60°C
Dimensions	144.8mm(L) x 85mm(W) x 45.2mm(H)
Weight	0.4 kg
Certifications	CE/FCC