

7. Specifications

LCD	Size	17.3"
	Resolution	1920 x 1080
	Contrast Ratio	700:1
	View Angle (Typ.)	178° (Horizontal) / 178° (Vertical)
	Brightness	300 cd/m ²
Video Input	HDMI x 2 SDI x 1 (Level A / Level B)	
Video Output	HDMI x 1 SDI x 1	
SDI Video Format	SMPTE-425M-A/B	1920x1080p 50/59.94/60
	SMPTE-274M	1920x1080p 23.98/23.98sf/24/24sf/25/25sf/29.97/29.97sf/30/30sf
	SMPTE-292M	1920x1080i 50/59.94/60
	SMPTE-296M	1280x720p 23.98/24/25/29.97/30/50/59.94/60
	SMPTE-259M	720x480i (NTSC), 720x576i (PAL)
HDMI Video Format	1920x1080p 50/59.94/60 1920x1080p 23.98/24/25/29.97/30 1920x1080i 50/59.94/60 1280x720p 23.98/24/25/29.97/30/50/59.94/60 720x480i (NTSC) 720x576i (PAL)	
Audio Input	SDI/HDMI Embedded Audio, 48 kHz sampling	
Audio Output	Analog stereo (Phone Jack) Speaker x 2 (3W x 2)	
Tally Input	Tally Port x 1	
Power	DC 12V/21.9W (12V/2A)	
Power Consumption	≤32 Watts	
Operating Temperature	0°C to 40°C (32°F to 104°F)	
Humidity	10 – 80%	
Weight	TLM-170V: 4.5 kg TLM-170VM: 6.7 kg TLM-170VR: 4.1 kg	