



# Syscom 421S

1800ft 4-to-1 wireless A&V transmission system  
Ultra-wide bandwidth specially designed for mega events

Part HL-SYSCOM 421S-2TX1RX Includes 2 Transmitters and 1 Receiver



1800ft



4 TX Synchronized A&V Transmission



RS422/485



USB Upgrade



Tally Function



Support RTSP Streaming

www.hollyland-tech.com



- Supports PTZ camera control
- Supports tally function
- Supports RTSP streaming
- Four TXs to one RX, ideal for multi-camera monitoring
- SDI and HDMI interfaces on both TX and RX
- 2000ft transmission distance and 0.07s latency

Item

Parameter

**Transmission latency**

≈ 0.07s

**Distance**

1800ft

**Power consumption**

TX<12W; RX<26W

**RX interface**

SDI output\*4 (BNC female); HDMI output\*4 (Type-A female);  
Antenna\*4 ( RP-SMA male); DC power input; USB-A; RJ45; RS422/485

**Dimensions (mm)**

TX: 88L\*30W\*144H; RX: 148L\*62W\*242H

**Weight**

TX: 380.5g; RX: 1574g (excluding antenna and battery buckle)

**Power supply**

TX DC input: 6-16V; RX DC input: 16-30V.

**TX interface**

SDI input (BNC female); HDMI input (Type-A female); 3.5mm Tally output;  
Antenna\*4 (RP-SMA male); DC power input; USB-C; RJ45; RS422/485