

Specifications		F-10A
LCD	Size	10"
	Resolution	1920×1080 (16:9)
	Pixel Pitch	0.11475(H) X 0.11475(W) mm
	Color Depth	16.7M
	Viewing Angle (Typ.)	160°(H)/160°(V)
	Luminance of white	300 cd/m ² (Max.)
	Contrast Ratio	1000 : 1
	Display Area	220.3(H)×123.9(V) mm
Input	1 X HDMI	HDMI 2.0 Input
	2 X BNC	3G-SDI * I/O integrated Chip
Output	1 X HDMI	HDMI 1.4 Output 1Ch
	1 X BNC	3G/HD/SD SDI Output 1Ch
Input Signal	3G-SDI	2.970Gbps
	HD-SDI	1.485Gbps
	SD-SDI	270 Mbps
	HDMI	480i / 480p / 576i / 576p / 720p / 1080i / 1080p / 2160p
SDI Input Signal Formats	SMPTE-425M-A/B	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF) 1080i(60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p (60/59.94/50)
	SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)	
Audio In	SDI Embedded Audio (Group, Ch Selectable)	
Audio Out	External Output Port (3.5m Phone Jack)	
Power	DC 6V / 2.5A , 34V / 0.5A	
Power Consumption (Approx.)	14W	
Operating Temperature	0°C to 40°C (32°F to 104°F)	
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	
Main Body Dimensions (mm/inch)	258 x 154 x 29.8(mm) / 10.15 x 6.06 x 1.17(inch)	
Box Dimensions (mm/inch)	320 x 240 x 87(mm) / 12.59x9.44x3.42 (inch)	
Weight	1.3kg / 2.86lbs	
Basic Accessories	BNC Connector, Camera Mount, D-Tap cable	
Optional Accessories	Ball Head, Camera Mount, Battery Bracket, V-mount, G-Mount, HDMI Bracket, Carrying Case, Acrylic Filter	

* The specification above may be changed without notice.

* When using a DC Adapter other than the one supplied by the manufacturer, please be advised that the adapter with DC 12V/3A ~ 6A can be compatible with the monitor.